

Sizes and Weights

Sizes and Weights

Square Feet of Door Area

Width	Height							
	6/8	7/0	7/6	8/0	8/6	9/0	9/6	10/0
1/0	6.7	7.0	7.5	8.0	8.5	9.0	9.5	10.0
1/6	10.0	10.5	11.3	12.0	12.8	13.5	14.3	15.0
1/8	11.1	11.7	12.5	13.3	14.1	15.0	15.8	16.7
1/10	12.2	12.8	13.8	14.7	15.6	16.5	17.4	18.3
2/0	13.3	14.0	15.0	16.0	17.0	18.0	19.0	20.0
2/2	14.4	15.2	16.2	17.3	18.4	19.5	20.6	21.7
2/4	15.6	16.3	17.5	18.7	19.8	21.0	22.2	23.3
2/6	16.7	17.5	18.8	20.0	21.3	22.5	23.8	25.0
2/8	17.8	18.7	20.0	21.3	22.7	24.0	25.3	26.7
2/10	18.9	19.8	21.3	22.7	24.1	25.5	26.9	28.3
3/0	20.0	21.0	22.5	24.0	25.5	27.0	28.5	30.0
3/2	21.1	22.5	23.8	25.3	26.9	28.5	30.1	31.7
3/4	22.2	23.3	25.0	26.7	28.3	30.0	31.7	33.3
3/6	23.3	24.5	26.3	28.0	29.8	31.5	33.3	35.0
3/8	24.4	25.7	27.5	29.3	31.2	33.0	34.8	36.7
3/10	25.6	26.8	28.8	30.7	32.6	34.5	36.4	38.3
4/0	26.7	28.0	30.0	32.0	34.0	36.0	38.0	40.0

Approximate weights per square foot:

1-3/8" Hollow Core 1.5 lbs.
 1-3/4" Hollow Core 1.6 lbs.
 1-3/4" Institutional 2.5 lbs.
 1-3/8" Wood Core 3.4 lbs.
 1-3/4" Wood Core 4.3 lbs.
 1-3/8" Particle Core 3.8 lbs.
 1-3/4" Particle Core 5.1 lbs.

LSL 3.8 lbs.
 1-3/4" Fire Core 4.8 lbs.
 1-3/8" Hollow Plastic 2.5 lbs.
 1-3/4" Wood Core Plastic 5.0 lbs.
 1-3/4" Particle Core Plastic 6.0 lbs.
 1-3/4" Fire Core Plastic 5.8 lbs.

Multiply square feet of door area by weight per square foot to obtain approximate weight of door.

MOHAWK
 FLUSH DOORS, INC.
PREMDOR

